

## LED DOWN LIGHT



## LOI-D2008

### Parameter table

Model No.	Power	Luminous Flux	CRI	LED TYPE	LED QTY	EMITING ANGLE	Light Size(mm) ( $\phi$ xH)(LxWxH)	Hole size(mm)
LOI-D2008-7W	7W	540-620LM	$\geq 80$	COB	1PC	33°	$\phi$ 90X50	$\phi$ 75-80
LOI-D2008-12W	12W	960-1100LM	$\geq 80$	COB	1PC	45°	$\phi$ 120X65	$\phi$ 95-100
LOI-D2008-20W	20W	1600-1800LM	$\geq 80$	COB	1PC	45°	$\phi$ 150X75	$\phi$ 125-130
LOI-D2008-35W	35W	2800-3200LM	$\geq 80$	COB	1PC	50°	$\phi$ 200X95	$\phi$ 180-185
LOI-D2008-50W	50W	4000-4500LM	$\geq 80$	COB	1PC	50°	$\phi$ 230X110	$\phi$ 205-210

### Parameters

Voltage	85-265V AC	Power factor	>0.9
Material	Aluminum + PMMA	Efficiency	>85
LED Chip	CITIZEN LED / LEDTEEN	Life Span	30000Hrs
Rated IP	IP20.For indoor use	CCT	White 6000K Natural White 4000K Warm White 3000K



# LOI-D2008

## Product details :

### Color temperature

