

LED SURFACE DOWN LIGHT



LOI-PC3003



Parameter table

Model No.	Power	Luminous Flux	CRI	LED TYPE	LED QTY	EMITING ANGLE	Light Size(mm) (ϕ xH)(LxWxH)	Hole size(mm)
LOI-PC3003-7W	7W	540-620LM	≥ 80	COB	1PC	23°/38°	ϕ 60X196	ϕ 20
LOI-PC3003-12W	12W	960-1100LM	≥ 80	COB	1PC	15°/24°/38°	ϕ 70X218	ϕ 20
LOI-PC3003-20W	20W	1600-1800LM	≥ 80	COB	1PC	15°/24°/38°	ϕ 100X218	ϕ 20

Parameters

Voltage	85-265V AC	Power factor	>0.9
Material	Aluminum + Glass	Efficiency	>85
LED Chip	CITIZEN LED / LEDTEEN	Life Span	30000Hrs
Rated IP	IP20.For indoor use	CCT	White 6000K Natural White 4000K Warm White 3000K



LOI-PC3003

Product details:

Color temperature



3000K

4000K

6000K



Stent
Prevent high voltage shore circuit
High temperature resistance 120°



Chip
JAPAN CITIZEN COB LED chip,
high CRI>80, high luminous
efficient>80m/w long
lifespan>50000hours



Reflector
Professional secondary
optical design, perfect
refraction



Lens & Housing
High transmittance and
beautifully designed