



# LOI-S1004

## Product details:

### Color temperature



# LED DOWN LIGHT



## LOI-S1004

### Parameter table

Model No.	Power	Luminous Flux	CRI	LED TYPE	LED QTY	EMITING ANGLE	Light Size(mm) ( $\phi$ xH)(LxWxH)	Hole size(mm)
LOI-S1004-7W	7W	540-620LM	$\geq 80$	COB	1PC	23°/38°/60°	$\phi$ 80X55	$\phi$ 70-75
LOI-S1004-12W	12W	960-1100LM	$\geq 80$	COB	1PC	15°/24°/38°/60°	$\phi$ 95X70	$\phi$ 80-85
LOI-S1004-20W	20W	1600-1800LM	$\geq 80$	COB	1PC	15°/24°/38°/60°	$\phi$ 125X90	$\phi$ 115-120
LOI-S1004-30W	30W	2400-2700LM	$\geq 80$	COB	1PC	15°/24°/38°/60°	$\phi$ 160X100	$\phi$ 145-150

### Parameters

Voltage	85-265V AC	Power factor	>0.9
Material	Aluminum + Glass	Efficiency	>85
LED Chip	CITIZEN LED / LEDTEEN	Life Span	30000Hrs
Rated IP	IP20.For indoor use	CCT	White 6000K Natural White 4000K Warm White 3000K